

REPORT ON
GEOTECHNICAL INVESTIGATIONS

FOR THE PROPOSED

**N. S. Bose Residential Hostel for
Secondary School, Chiraila,
Block Rajauli, Dist. Nawada**

Your Letter No.- BSEIDC/Tech/1960 (P)/2018-7919 Dated – 22.11.2021
[SL. No. – 5]

Submitted to
The Chief Engineer
BSEIDC, Patna

December, 2021



BIHAR FOUNDATION CONSULTANTS

[A unit of Baidyanath Foundation Consultants Pvt. Ltd.]

Having an

NABL Accredited / ISO 9001: 2015 Certified Laboratory

Ganga Darshan Apartment, Flat No. 403.

Patna – 10

[e-mail : bifcon.pat@gmail.com, Phone No: + 91612 – 2272826]

N. S. Bose Residential Hostel for Secondary School, Chiraila, Block Rajauli, Dist. Nawada



Bihar Foundation Consultants
403, Ganga Darshan Apartment, Patna-10
[A Unit : Baidyanath Foundation Consultants Pvt. Ltd.]

PN - 211218

CONTENTS

<u>Sl.No.</u>	<u>Description</u>	<u>Page No.</u>
1	Introduction	1
2	Field Work	1
3	Laboratory Test	2
4	Presentation of Test Results	2
5	Soil Stratification	2
6	Foundation Analysis	2
7	Recommendations	3-4

Appendix

[Containing Figures and Tables]

- A. Bore Holes Location Map
- B. Field Test Observations & Laboratory Test Results
- C. Graph of Grain size Analysis
- D. Triaxial shear / Direct shear strength test curves
- E. 'e-log p' Curves from Consolidation Tests [Not required]
- F. Sample calculation of pile
- G. Copy of Work Oder

INTRODUCTION

The subsoil investigations reported herein were taken up (vide W.O. No. [BSEIDC/Tech/1960\(P\)/2018-7919 Dated – 22.11.2020 \[SL. No. 5\]](#) to find out the nature of subsoil at the site of the proposed construction and to recommend the capacity and type of its foundation. After certain tests on the soil, as detailed below, the desired recommendations have been made on **page 3-4** of this Report.

2. FIELD WORK

The fieldwork consisted of sinking bore holes, collecting soil samples and conducting the necessary field tests.

2.1. Boring

Taking guidance from IS: 1892, 150 mm diameter bore holes were sunk at locations shown in the bore hole location map.

2.2 Sampling

2.2.1 Undisturbed Soil Samples

Open drive samplers of 100-mm diameter and about 450-mm length were used for obtaining undisturbed samples of cohesive soils. The collection, sealing, labeling and transportation of the samples to the laboratory were done as per the IS guide-lines.

2.2.2 Disturbed Soil Samples

Disturbed soil samples were collected at suitable intervals of depth (not more than 2.5 m) and at all depths of change in the nature of the subsoil. These samples were sealed in polythene bags with proper identification labels.

2.3 Field Tests

2.3.1 Standard Penetration Tests (SPT)

These tests were conducted as per IS: 2131 – 1963. The depth interval between two consecutive tests was 1 to 1.5 m. The tests were located in between the levels at which undisturbed soil samples were collected.

3. LABORATORY TESTS

Some or all of the following laboratory tests, as necessary, were done on the collected soil samples. Representative soil samples were selected for this from the different soil strata encountered during boring. The tests were performed as per the relevant Indian Standard Codes of Practice.

- (a) Natural moisture content
- (b) Bulk density
- (c) Grain size analysis (using sieves and / or hydrometer)
- (d) Specific gravity of soil solids
- (e) Atterberg's limit tests (liquid, plastic and shrinkage limits)
- (f) Shear Tests :
 - [I] Triaxial compression test (unconsolidated – undrained), generally for fine- grained soils
 - [II] Unconfined compression tests, only on cohesive soils
 - [III] Direct shear tests, generally for coarse-grained soils
- (h) Other tests as and when required.

4. PRESENTATION OF TEST RESULTS

The field and laboratory test results are given in the **Appendix B**.

5. SOIL STRATIFICATION

The results of field tests in three bore holes sunk at the site [vide Location Sketch in App. A] and the results of laboratory tests conducted on the collected soil samples indicate that the soil stratification at the site is as describe below.

The subsoil in BH 1 and 2 is sandy clayey silt [type ML], and in BH 2 it is clayey silty sand [type SC-SM] up to the depth of about 3.0 m then follows sandy silty clay [type CL] up to the investigated depth of 10.5 m bgl.

Ground water table was struck at about 5.10 m to 5.20 m depth below GL in December, 2021 It is subject to seasonal variations.

6. FOUNDATION ANALYSIS

The safe capacity of foundation of any type and size may be determined on the basis of the soil data given in this Report by using the standard methods of foundation design and following the relevant Indian Standard Codes.

7. RECOMMENDATIONS

The design of the foundation for the proposed structure depends on the nature of both [a] the subsoil and [b] the structure.

The subsoil in BH 1 and 2 is sandy clayey silt [type ML], and in BH 2 it is clayey silty sand [type SC-SM] up to the depth of about 3.0 m then follows sandy silty clay [type CL] up to the investigated depth of 10.5 m bgl.

Ground water table was struck at about 5.10 m to 5.20 m depth below GL in December, 2021 It is subject to seasonal variations.

Hence,

1. The subsoil is loose silt up to about 2 m depth. Hence the proposed structure may be provided with shallow foundation at a depth of 2.0 m or more.
2. The subsoil up to 4 m is silt dominating. Hence placement of U/R pile may not be desirable as the top formation may collapse during pile placement. Hence plane piles of lengths 4.0 m to 10.0 m with shaft diameters 0.25 m, 0.30 m, 0.40 m and 0.50 m may be provided. A casing will have to be used during boring for the pile.

By way of example, the values of safe capacities of

[1] Shallow foundations and [2] Plane piles of the above mentioned sizes and depths have been calculated (vide Samples of Calculations in Appendix F) and the safe capacities are given below in Tables 1 and 2 respectively.

Table 1: Allowable Net Bearing Pressures [q_{na}] and Settlements Expected [s]

Depth (m) below Ground Level	Width (m)	Net allowable bearing pressure (t/m^2)			Maximum expected settlement (mm)
		Strip footing	Square footing	Raft footing	
2.0	2	5.7	5.8	...	50
	3	4.7	4.7	...	50
	10	6.7	75
2.5	2	6.7	6.9	...	50
	3	5.8	5.8	...	50
	10	7.0	75
3.0	2	7.5	8.1	...	50
	3	7.4	7.4	...	50
	10	7.2	75
3.5	2	8.7	9.3	...	50
	3	8.5	8.5	...	50
	10	8.5	75
4.0	2	10.0	10.4	...	50
	3	9.5	9.5	...	50
	10	8.8	75

Table 2. Safe Capacities of Plane Piles
[Factor of safety = 2.5 in skin friction and 3 in bearing]

Pile length [m]	Safe Capacities [tonnes] (SUBJECT TO CHECKING FOR SLENDERNESS RATIO*) for Piles of diameters (m):			
	0.25 m	0.30 m	0.40 m	0.50 m
4.0	1.9	2.5	3.8	5.2
6.0	4.8	6.0	8.6	11.5
8.0	8.0	10.0	14.1	18.7
10.0	11.2	13.9	19.6	25.8


*For a preliminary checking of the slenderness ratio, the modulus of subgrade reaction (k) may be estimated from the following empirical relation given in IS: 2950-1981 (Second Revision) Table 1. $k \text{ (kN/m}^3\text{)} = 240 c$, where $c \text{ (kN/m}^2\text{)}$ is the value of cohesion of the soil at the concerned depth. **Notes:**

1. If a subsoil condition much different from those reported herein is met with during foundation trenching or piling, suitable steps should be taken.
2. If the depth of a shallow foundation is below the water table, dewatering of the foundation trench has to be done, and its side walls may have to be suitably supported at the time of the construction of the foundation.
3. In case a basement is being provided, its base and side walls have to be safeguarded against the likely ingress of ground-water.
4. If concreting for a pile has to be done under water, DMC and tremie method of concreting should be adopted.
5. As per the provisions of the IS Code, **an appropriate number of piles must be subjected to routine load tests to check the veracity of the above recommended values of the safe capacities of piles.**

For Bihar Foundation Consultants

(Prof. C.N. Sinha, Dr.-Ing., FIE)
Chief Consultant.

N. S. Bose Residential Hostel for Secondary School, Chiraila, Block Rajauli, Dist. Nawada



Bihar Foundation Consultants
 403, Ganga Darshan Apartment, Patna-10
 [A Unit : Baidyanath Foundation Consultants Pvt. Ltd.]

PN - 211218

Appendix - A

NAME OF WORK : Sub soil Investigation for C/O						BORING FINISH DATE : 19.12.2021		WATER TABLE : 5.10 m bgl										
N. S. Bose Residential Hostel for Secondary School, Chiraila, Block Rajauli, Dist. Nawada				BORING METHOD : Rotary														
BORE HOLE NO. : 1		Site Incharge - Mukesh Singh		TERMINATION DEPTH : 10.5 m		RECORD ON : 19.12.2021												
Depth Below GL (m)	Sample No.	SPT 'N' Value observation	Visual Description of Soil with IS Classification	Depth(m)		Thickness (m)	Liquid Limit	Plastic Limit	Plasticity Indx, %	Bulk Density (gm/cm3)	Natural Moisture Content (%)	Specific Gravity	Shear Test			Compression Index (C _c)		
		Obsr.		from	to								Type of Test	Cohesion, c (kg/cm ²)	Friction Angle, φ°			
1.0			Greyish sandy clayey silt, ML	0.0		3.0												
1.5	S1	5						26.8	21.9	4.9	1.94	28.9	2.66		0.06	14.6		
2.5																		
3.0	S2	6			3.0						1.94	28.8	2.66		0.06	15.1		
4.0			Greyish sandy silty clay, CL	3.0		7.5												
4.5	S3	7						30.9	22.8	8.1	1.97	28.0	2.70		0.35	4.1		
5.5																		
6.0	S4	9									1.99	26.6	2.70		0.44	5.0		
7.0																		
7.5	S5	10						31.1	14.3	16.8	2.00	26.0	2.70		0.48	5.0		
8.5																		
9.0	S6	11									2.01	25.4	2.70		0.51	5.1		
10.0																		
10.5	S7	15			10.5						2.01	25.3	2.70		0.63	5.1		

NAME OF WORK : Sub soil Investigation for C/O						BORING FINISH DATE : 19.12.2021		WATER TABLE : 5.20 m bgl											
N. S. Bose Residential Hostel for Secondary School, Chiraila, Block Rajauli, Dist. Nawada						BORING METHOD : Rotary													
BORE HOLE NO. : 2		Site Incharge - Mukesh Singh				TERMINATION DEPTH : 10.5 m		RECORD ON : 19.12.2021											
Depth Below GL (m)	Sample No.	SPT 'N' Value observation	Visual Description of Soil with IS Classification	Depth(m)		Thickness (m)	Liquid Limit	Plastic Limit	Plasticity Indx, %	Bulk Density (gm/cm3)	Natural Moisture Content (%)	Specific Gravity	Shear Test			Compression Index (C _c)			
		Obsr.		from	to								Type of Test	Cohesion, c (kg/cm ²)	Friction Angle, φ°				
1.0			Greyish sandy clayey silt, ML	0.0		3.0													
1.5	S1	4									1.94	28.9	2.66		0.05	14.2			
2.5																			
3.0	S2	6			3.0			25.1	21.9	3.2	1.94	28.8	2.66		0.06	15.1			
4.0			Greyish sandy silty clay, CL	3.0		7.5													
4.5	S3	8									1.98	27.4	2.70		0.40	4.6			
5.5																			
6.0	S4	10						27.9	20.6	7.3	2.00	26.0	2.70		0.48	5.0			
7.0																			
7.5	S5	12									2.01	25.4	2.70		0.55	5.1			
8.5																			
9.0	S6	14						31.2	22.4	8.8	2.01	25.3	2.70		0.61	5.1			
10.0																			
10.5	S7	16		10.5					2.02	24.7	2.70		0.65	5.1					

NAME OF WORK : Sub soil Investigation for C/O						BORING FINISH DATE : 20.12.2021		WATER TABLE : 5.20 m bgl											
N. S. Bose Residential Hostel for Secondary School, Chiraila, Block Rajauli, Dist. Nawada				BORING METHOD : Rotary															
BORE HOLE NO. : 3		Site Incharge - Mukesh Singh				TERMINATION DEPTH : 10.5 m		RECORD ON : 20.12.2021											
Depth Below GL (m)	Sample No.	SPT 'N' Value observation	Visual Description of Soil with IS Classification	Depth(m)		Thickness (m)	Liquid Limit	Plastic Limit	Plasticity Indx,%	Bulk Density (gm/cm3)	Natural Moisture Content (%)	Specific Gravity	Shear Test			Compression Index (C _c)			
		Obsr.		from	to								Type of Test	Cohesion, c (kg/cm ²)	Friction Angle, φ°				
1.0			Greyish clayey silty sand, SC-SM	0.0		3.0													
1.5	S1	4									1.91	30.0	2.62		0.00	28.0			
2.5																			
3.0	S2	5			3.0						1.91	30.1	2.63		0.00	28.0			
4.0			Greyish sandy silty clay, CL	3.0		7.5													
4.5	S3	7						30.5	22.7	7.8	1.97	28.0	2.70		0.35	4.1			
5.5																			
6.0	S4	9									1.99	26.6	2.70		0.44	5.0			
7.0																			
7.5	S5	13						30.8	22.5	8.3	2.01	25.4	2.70		0.59	5.1			
8.5																			
9.0	S6	12									2.01	25.4	2.70		0.55	5.1			
10.0																			
10.5	S7	15					10.5				2.01	25.3	2.70		0.63	5.1			

Table 2 [part B]: Grain Size Analysis Results

[for Bore hole No./ Depth in m shown thus: 1/1.5]




Table 2 [part B]: Grain Size Analysis Results

[for Bore hole No./ Depth in m shown thus: 1/1.5]












Table 2 [part B]: Grain Size Analysis Results

[for Bore hole No./ Depth in m shown thus: 1/1.5]



TRIAXIAL / DIRECT SHEAR TEST PLOTS










**Bihar Foundation Consultants,
[A unit of Baidyanath Foundation Consultants Pvt. Ltd.]**

Project No. 211218








For the Proposed

N. S. Bose Residential Hostel for Secondary School,
Chiraila, Block Rajauli, Dist. Nawada

TRIAXIAL / DIRECT SHEAR TEST PLOTS



TRIAXIAL / DIRECT SHEAR TEST PLOTS



Report on Sub Soil Investigation for the proposed Construction of

N. S. Bose Residential Hostel for Secondary School, Chiraila,
Block Rajauli, Dist. Nawada

SAMPLE CALCULATION OF BEARING CAPACITY OF SHALLOW FOUNDATION

The determination of the **net safe bearing capacity**, q_{ns} , is done first on the basis of the shear failure criterion after dividing the value of the **net ultimate bearing capacity** q_{nf} , calculated as described below, by a suitable factor of safety. The **net soil pressure**, q_s , for a given permissible settlement is then calculated as explained in the next section. The lower of the two values, q_{ns} and q_s , thus determined is taken as the **allowable bearing capacity** of the soil.

1. Shear Failure Criterion. The **net ultimate bearing capacity** q_{nf} (t/m^2) of a shallow foundation of breadth B (m) and depth D (m) is given as per IS:6403-1981 (Sec.5.1.2) by the following equation :

$$q_{nf} = c N_c s_c d_c I_c + q (N_q - 1) s_q d_q I_q + 0.5 \gamma B N_\gamma s_\gamma d_\gamma I_\gamma w$$

where c = cohesion (t/m^2)
 q = effective surcharge (t/m^2)
 γ = unit weight of subsoil (t/m^3)
 N_c, N_γ, N_q = bearing capacity factors, which are functions of ϕ , the angle of internal friction of the soil
 s_c, s_q, s_γ = shape factors
 d_c, d_q, d_γ = depth factors
 I_c, I_q, I_γ = inclination factors
 w = water table factor (= 0.5 to 1.0) depending on the depth, D_w of water table- vide Table below.

} related to cohesion, surcharge and density of subsoil respectively

The bearing capacity factors (N 's) are functions of ϕ , the angle of internal friction of the soil. Their values are found for general shear failure by referring to standard tables. If subsoil conditions are such as to lead to local shear failure, the values of these factors are found for a reduced value of angle of internal friction (ϕ') given by the equation : $\tan \phi' = 0.67 \tan \phi$. The value of cohesion is also reduced to $c' = 0.67 c$.

The values of the other factors for usual conditions are as tabulated below :

$s_c =$	1.3	$1+0.2B/L$	1	$d_c =$	$1+0.2(N\phi)^{0.5} D/B$	D_w at	G.L.	Fou'dn.Level
$s_q =$	1.2	$1+0.2B/L$	1	$d_q = d_\gamma =$	1	$w =$	0.5	1
$s_\gamma =$	0.8//0.6	$1-0.4B/L$	1	$d_q = d_\gamma =$	$1+0.1(N\phi)^{0.5} D/B$	Interpolation between these values is linear.		
FOR	$s_q // O$	Rect.	STRIP	$I_c, I_q, I_\gamma = 1$ for vertical load				

In the present case, the representative values of cohesion c and angle of internal friction (ϕ) of the soil may be obtained from the soil data given earlier.

One example of calculation for a certain depth and width of a strip or square footing is given in the **Table A** on the next page. Full submergence of the soil has been assumed. The **safe bearing capacity**, q_{ns} has been obtained by dividing q_{nf} by a **safety factor**, 3. The net safe bearing capacity for a footing of the selected size and depth of footing is to be seen in its last column. Calculations of safe bearing capacities for other depths and widths of footings are done similarly.

2 Calculation of allowable bearing capacity based on settlement criterion

The **net soil pressure**, q_s (t/m^2) for a permissible settlement of 25 mm is give by Teng's formula:

$$q_s = 3.5 [N'' - 3] \left[\frac{(B + 0.3)}{2B} \right]^2 w' F_d \quad t/m^2$$

where N'' = corrected value of N from SPT

$$F_d = [1 + D/B] < \text{or} = 2$$

D, B and w' are as defined before.

**Report on Sub Soil Investigation for the proposed Construction of
N. S. Bose Residential Hostel for Secondary School, Chiraila,
Block Rajauli, Dist. Nawada**

For a permissible settlement of S mm, the allowable bearing capacity

$$q'_s = S q_s / 25$$

The corrected SPT N'' values used in the calculations based on the above formula for different depths below G.L. may be found from the recorded data.

The N'' value used in any case is to be for the influence zone below the footing, which depends on its width. A sample of calculation of the allowable soil pressure for the chosen size and depth of footing and for the permissible settlement is given in **Table B** in the next section.

The net allowable bearing pressure will be the lower of the values of bearing pressures found in the two Tables A and B.

Table A

Calculation of Net Safe Bearing Pressure [based on shear failure criterion]

Shape of Foundation:			F.S.=	$\gamma, t/m^3=$		$c =$	$\phi =$	$N_c =$	$N_q =$	$N_\gamma =$
STRIP			3	1.94		0.6	14.6	10.73	3.79	2.50
D [m]	B [m]	dc	dq = dg	c	q	I Term	II Term	III Term	qnf	qnf /F
2	2	1.26	1.129	0.6	1.94	8.10	6.12	2.73	16.96	5.65

Table B

Calculation of Net Allowable Bearing Pressure [based on settlement criterion]

D	B	Fd =	N''	w'	$q_{s=25}$ t/m ²	S mm	$q_{s=S}$ t/m ²
m	m						
2	2.0	2	5.5	0.5	2.893	50	5.7859

The adjoining Table and the comments below it are for a footing of depth, **D = 2 m, and width, B [m] = 2.0**

The value of allowable bearing pressure from the above Table for $s = 50$ mm is = **5.8 t/m²**

The value of safe bearing capacity from shear criterion as found from Table A

= **5.7 t/m²**

Hence the allowable bearing pressure for settlement, $s =$ or < 50 mm will be = **5.7 t/m²**

The calculations for other depths and widths of footing are similar.

Calculations of Capacity of Plane Pile for the proposed
N. S. Bose Residential Hostel for Secondary School, Chiraila, Block Rajauli, Dist. Nawada

Based on IS:2911 (Part I, Sec. 2) 2010, Annex B, (Clauses 6.3.1.1 and 6.3.2)

using both cohesion (c), in t/m² and angle of internal friction (φ°).

WHEN Pile diameter, D (m) = **0.25** Area of pile base, A_p (m²) = 0.049 & circumference (in m) of pile base, j = 3.14 x D = 0.785
Surface area of pile's contact with soil, A (m²) = j x t where t = thickness of soil layer in contact with pile.

In **CLAY**: Skin friction in clay, Q_s = c A ,
where Reduction factor, α depends on c, as given in Fig. 2 of Annex. B of the above IS Code:2911
End bearing, Q_b = A_p C_p N_c,
where N_c=9

In **SAND**: Skin friction, Q_s = K P_{mid} A tan δ, where K = 1.5
and δ = . **End bearing, Q_b = A_p(0.5 D_γ N_γ + P_{tip}N_a),**
where P = overburden press. at mid-layer or pile tip , as the case be,
and the values of N_q and N_γ are to be taken from the IS Code.
*Max'm permissible P[t/m²] = 15 to 20 X pile diameter (D) X γ_{sub}
= 3.75 to 5 X γ_{sub} t/m².
3.525 to 4.7 t/m .

Let factor of safety in
Total Ultimate capacity of pile, Qu = Q_s + Q_b.
Sate capacity of pile, Q_{st} = (Q_s /f_s + Q_b/f_b)
friction, f_s = 2.5
bearing, f_b = 3.0

Depth of soil layer (m)	Soil type	γ _{sub} t/m ³	c t/m ²	α	φ	t [m]	p = γ x t	P _{tip}	Permissible		A = j x t m ²	Qs' (for 1 layer) t	Qs = ΣQs' t	Qb t	Qu t	Qsf [runded off] tonnes	Pile Length m
							t/m ²	=Σp t/m ²	P _{tip} t/m ²	P _{mid} t/m ²	t	t	t	t			
0.0-0.5	sandy clayey silt					0.5	0.00	0.00	0.0	0.0	Not considered due to cut-off and very soft layers.					0.5	
0.5-2.0	sandy clayey silt	0.94	0.50	1.00	14.20	1.5	1.41	1.41	1.4	0.7	1.18	0.90	0.90	0.52	1.42		2.0
2.0-4.0	sandy clayey silt	0.94	0.55	1.00	14.65	2.0	1.88	3.29	3.3	2.4	1.57	2.31	3.21	1.99	5.20	1.9	4.0
4.0-6.0	sandy silty clay	0.98	3.95	1.00	4.55	2.0	1.96	5.25	3.5	3.5	1.57	6.86	10.07	2.33	12.40	4.8	6.0
6.0-8.0	sandy silty clay	0.99	4.65	0.95	5.00	2.0	1.98	7.23	3.5	3.5	1.57	7.66	17.74	2.66	20.40	8.0	8.0
8.0-10.0	sandy silty clay	1.00	5.40	0.82	5.10	2.0	2.00	9.23	3.5	3.5	1.57	7.69	25.43	2.97	28.40	11.2	10.0

Depth,d	γ _{sub}	φ°	* N _γ	Qb for φ	* N _q	# Qb	Qb for c	# Qb
4.0	0.98	4.55	0.40	1.51	0.25	3.95	1.74	
6.0	0.99	5.00	0.45	1.57	0.27	4.65	2.05	
8.0	1.00	5.10	0.46	1.58	0.28	5.40	2.38	
10.0	1.00	5.10	0.46	1.58	0.28	6.10	2.69	

N. S. Bose Residential Hostel for Secondary School, Chiraila, Block Rajauli, Dist. Nawada



बिहार राज्य शैक्षणिक आधारभूत संरचना विकास निगम लिमिटेड
BIHAR STATE EDUCATIONAL INFRASTRUCTURE DEVELOPMENT CORPORATION LTD.

(A Govt. of Bihar Undertaking)

ISO 9001:14001; OHSAS 18001

Shiksha Bhawan, Bihar Rashtrabhasha Parishad Campus, Acharya Shivpujan Sahay Path, Saidpur, Patna - 800 004

Tel. No. : 0612 - 2660850 • Fax No. : 0612 - 2660256

E-mail : bseidc@gmail.com • Website : <http://www.bseidc.in> • CIN : U80301BR2010SGC015859

पत्रांक:- BSEIDC/TECH/1960/2018 - 7919

दिनांक 22/11/2021

प्रेषक,

मुख्य अभियंता
BSEIDC Ltd, Patna

सेवा में,

बिहार फाउंडेशन कंसल्टेन्ट
गंगा दर्शन अपार्टमेंट, फ्लैट नं०-403,
सदाकत आश्रम के पश्चिम,
पटना- 800010

विषय:- निर्माण स्थल के मिट्टी जाँच हेतु।

प्रसंग:- भवन निर्माण विभाग का पत्र संख्या-2030, दिनांक-21.04.2006

महाशय,

बिहार राज्य शैक्षणिक आधारभूत संरचना विकास निगम लि० के अधीन " औरंगाबाद, मुजफ्फरपुर, बांका, गया एवं नवादा " में आवासीय छात्रावास का निर्माण कार्य प्रस्तावित है। इस भवन के निर्माण स्थल पर मिट्टी की जाँच कराना है।

अतः अनुरोध है कि उपरोक्त स्थल का तीन बिन्दुओं पर 10.5 मीटर गहराई तक प्रत्येक 1.5 मीटर गहराई में मिट्टी का नमूना संग्रह कर प्रतिवेदन समर्पित करें। साथ ही विहित प्रपत्र में मिट्टी के भार वहन क्षमता की गणना (Isolated एवं Pile Foundation के लिए अलग-अलग) भी Hard Copy एवं Soft Copy में समर्पित करें।

इस जाँच कार्य को इस तरह संपादित करें कि ट्रान्सपोर्टेशन एवं मोबलाईजेशन खर्च कम से कम हो। कार्य स्थल पर सम्पर्क व्यक्ति, कार्य से संबंधित प्राचार्य / संबंधित कार्यपालक अभियंता रहेंगे।

विश्वासभाजन

मुख्य अभियंता

Bihar Foundation Consultants
403, Ganga Darshan Apartment, Patna-10
[A Unit : Baidyanath Foundation Consultants Pvt. Ltd.]

PN - 211218

Appendix - G1

N. S. Bose Residential Hostel for Secondary School, Chiraila, Block Rajauli, Dist. Nawada

(32)

नेताजी सुभाष चन्द्र बोस आवासीय छात्रावास निर्माण हेतु प्रस्तावित विद्यालयों के नाम एवं भूमि की विवरणी:

क्रमांक	जिला का नाम	प्रखंड का नाम	आवासीय छात्रावास से संबंधित विद्यालय का नाम	उपलब्ध भूमि की विवरणी (खाता सं०, खेसरा एवं रकबा सहित)
1	औरंगाबाद	नवीनगर	उच्च माध्यमिक विद्यालय, बेला	खाता सं०- 71, 132 प्लॉट न० 370, 369, 366, 1028 एराजी - 01 एकड़ 80 डिसमिल थाना सं०- 192, तौजी- 2802
2	मुजफ्फरपुर	साहेबगंज	राजकीयकृत उच्चतर म० वि० साहेबगंज	खाता सं०- पुराना- 56 खेसरा - पुराना- 1333, 1334 खाता सं०- नया- 494 खेसरा सं०- नया - 1520, 1521 रकबा - 06 एकड़ 50 डिसमिल लगभग।
3	बांका	बांका	प्र० म० वि० चक्काडीह	खाता- 153, 449 खेसरा - 508, 614 रकबा - 01 एकड़ 11 डिसमिल
4	गया	मोहनपुर	म० वि० जेठुआ डाहा	रकबा - 3 एकड़ 64 डिसमिल
5	नवादा	रजौली	म० वि० चिरैला	खाता (नया) - 58 प्लॉट- 651, 652 पुराना- 98, प्लॉट- 725, 726, 732, 733 एवं 734 रकबा- 3 एकड़ 36 डिसमिल

*Account
21/09/2021
EE, SLO.*

Bihar Foundation Consultants
403, Ganga Darshan Apartment, Patna-10
[A Unit : Baidyanath Foundation Consultants Pvt. Ltd.]